



## SIM7600X-H

SIM7600X-H is a complete multi-band LTE-FDD/LTE-TDD/HSPA+/UMTS/EDGE/GPRS/GSM module solution in LCC type which supports LTE CAT4 up to 150Mbps for downlink and 50Mbps for uplink data transfer. Designed in the compact and unified form factor, SIM7600X-H is compatible with SIMCom HSPA+ SIM5360 module/LTE CAT1 SIM7600X and LTE CAT3 SIM7100 module, which allows customer to design their application once for different technology and benefit from great development time-saving.

## Smart Machine Smart Decision

### Variant for EMEA/Korea/Thailand

#### SIM7600E-H:

- LTE-TDD B38/B40/B41
- LTE-FDD B1/B3/B5/B7/B8/B20
- UMTS/HSPA+ B1/B5/B8
- GSM/GPRS/EDGE B3/B8

### Variant for North America

#### SIM7600A-H:

- LTE-FDD B2/B4/B12
- UMTS/HSPA+ B2/B5

#### SIM7600V-H:

- LTE-FDD B2/B4/B5/B13

### Variant for Australia/New Zealand/South America

#### SIM7600SA-H:

- LTE-TDD B40
- LTE-FDD B1/B2/B3/B4/B5/B7/B8/B28
- UMTS/HSPA+ B1/B2/B5/B8
- GSM/GPRS/EDGE 850/900/1800/1900MHz

### Variant for Japan

#### SIM7600JC-H:

- LTE-FDD B1/B3/B8/B18/B19/B26

### General features

- LCC Package
- Control Via AT Commands
- Supply voltage range: 3.4V~ 4.2V, 3.8V Typical
- Operation temperature: -40°C to +85°C
- Dimension: 30\*30\*2.9mm
- Weight: 5.7g
- Bandwidth: 1.4/3/5/10/15/20MHz
- 3GPP E-UTRA Release 11

### Specifications for Data transfer

- LTE CAT4
  - Uplink up to 50Mbps
  - Downlink up to 150Mbps
- HSPA+
  - Uplink up to 5.76 Mbps
  - Downlink up to 42 Mbps
- UMTS
  - Uplink/Downlink up to 384Kbps
- EDGE
  - Uplink/Downlink up to 236.8Kbps
- GPRS
  - Uplink/Downlink up to 85.6Kbps

### Other features

- USB Driver for Microsoft Windows 2000/XP/Vista/Win7/Win8/Win10
- USB Driver for Linux /Android
- RIL supporting for Android 2.4/4.0/5.0/6.0/7.0
- MBIM to Win8
- Firmware update via USB
- TCP/IP/IPV4/IPV6/Multi-PDP/FTP/FTPS /HTTP/HTTPS/SMTP/SMTSP/DNS
- SSL3.0/TLS1.0/TLS1.2
- DTMF (Sending and Receiving)
- Audio Playing
- USB Audio and VoLTE
- FOTA
- eCall\*

### Interfaces

- USB2.0 with High speed up to 480Mbps
- UART
- GPIO
- Antenna: Solder pads for Primary, Rx-diversity and GNSS antennas
- (U)SIM card (1.8V/3.0V)
- Digital Audio through PCM
- MMC/SD
- SDIO
- ADC
- GNSS: GPS/GLONASS/Beidou/Galileo\*

### Approvals

- RoHS Compliant
- CE(SIM7600E-H/SIM7600SA-H\*)
- FCC/PTCRB/AT&T\*(SIM7600A-H)
- FCC\*/GCF\*/Verizon\*(SIM7600V-H)
- ACMA\* (SIM7600SA-H)
- JATE/TELEC(SIM7600JC-H)

\*Under Development/Testing

More about SIMCom SIM7600X-H

Please contact:

Tel: 86-21-32523300

Fax: 86-21-32523301

Email: [simcom@sim.com](mailto:simcom@sim.com)

Website: [www.simcomm2m.com](http://www.simcomm2m.com)